



US009636966B2

(12) **United States Patent**
Imazu et al.

(10) **Patent No.:** **US 9,636,966 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **STABILIZER BUSHING**

(56) **References Cited**

(71) Applicant: **TOYO TIRE & RUBBER CO., LTD.**,
Osaka-shi, Osaka (JP)

U.S. PATENT DOCUMENTS

(72) Inventors: **Eiichi Imazu**, Osaka (JP); **Yoshiyuki Saihara**, Osaka (JP)

3,464,656 A * 9/1969 Boden F16F 1/38
16/109
6,513,801 B1 * 2/2003 McCarthy B60G 21/0551
267/141.1
2006/0091595 A1 5/2006 Hayashi et al.
(Continued)

(73) Assignee: **TOYO TIRE & RUBBER CO., LTD.**,
Osaka (JP)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

CN 1766362 A 5/2006
CN 1875204 A 12/2006
(Continued)

(21) Appl. No.: **14/678,185**

OTHER PUBLICATIONS

(22) Filed: **Apr. 3, 2015**

Office Action dated Nov. 2, 2016, issued in Chinese Patent Application No. 201510162175.7 with English Translation (15 pages).

(65) **Prior Publication Data**

US 2015/0290997 A1 Oct. 15, 2015

Primary Examiner — Melanie Torres Williams

(30) **Foreign Application Priority Data**

Apr. 11, 2014 (JP) 2014-081678

(74) *Attorney, Agent, or Firm* — Westerman, Hattori, Daniels & Adrian, LLP

(57) **ABSTRACT**

(51) **Int. Cl.**

B60G 21/055 (2006.01)

F16F 1/16 (2006.01)

(52) **U.S. Cl.**

CPC **B60G 21/0551** (2013.01); **F16F 1/16**
(2013.01); **B60G 2202/135** (2013.01); **B60G 2204/1222** (2013.01); **B60G 2204/41** (2013.01)

(58) **Field of Classification Search**

CPC .. B60G 21/055; B60G 21/0551; B60G 11/24;
B60G 2022/135; B60G 2204/1222; B60G 2204/41; F16F 1/38; F16F 1/16
USPC 267/293, 189, 276, 141.1; 280/124.13,
280/124.77, 124.107

See application file for complete search history.

When a clipping member is fitted onto the outer peripheral surface of a sealing member, the tightening margin for elastic fitting is provided to the sealing member by the fastening force of the clipping member. In this case, the clipping member includes an opening portion formed to have a partial separation in the circumferential direction and is formed from a metallic material approximately in a C shape having an inner diameter smaller than the outer diameter of the sealing member. Also in the case where a permanent set occurs in the rubber elastic body (the sealing member) as time passes, the clipping member is reduced in diameter by the elastic restoring force of itself. Accordingly, the tightening margin for elastic fitting to the stabilizer bar can be continuously provided to the sealing member.

14 Claims, 6 Drawing Sheets

